

linea xs / xc leader cable

Dimensions

Metric:
1525 mm, 3050 mm, 9150 mm, 15250 mm (X)
Imperial
60.04 in, 120.08 in, 360.24 in, 600.40 in (X)

Technical Data

Outer cable diameter	11 mm | 0.44 in
Outer diameter connector	30 mm | 1.19 in
Minimum bending radius Cable (fixed installation)	4x Outer Ø
Minimum bending radius cable (flexible)	15x Outer Ø
Environment	Indoor, Outdoor
Ingress protection rating	IP66
Ambient temperature (Operation)	-40 °C to 80 °C | -40 °F to 176 °F
Approbation	ETL, CE
	Designed and Developed in Bavaria. Made in Germany.

sales@biontechnologies.com
www.biontechnologies.com
Phone:
(DE) +49 8231 95787 0

All information without guarantee. Errors, changes and misprints excepted.

linea xs / xc leader cable

Configurator

LIN-XSXC-LEAD -(1)_____ -(2)_____-Y01

1 Dimension	
1525	1525 mm / 60.04 in
3050	3050 mm / 120.08 in
9150	9150 mm / 360.24 in
15250	15250 mm / 600.39 in

2 Wiring configuration	
NDIM	NDIM / IOT
0-10V	0 - 10V
DMX	DMX
EXT	EXT

sales@biontechnologies.com
www.biontechnologies.com
Phone:
(DE) +49 8231 95787 0

All information without guarantee. Errors, changes and misprints excepted.