



# funis m round 2000

pureWhite

SPECIFICATION SHEET

## BION TECHNOLOGIES GMBH

Lindberghstrasse 15  
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0  
Fax: +49 (0)8231/95787-29

[www.biontechnologies.com](http://www.biontechnologies.com)  
[info@biontechnologies.com](mailto:info@biontechnologies.com)

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH  
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm



## Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

FUN-M-R-20- \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - Y01

TYP - LUMINOUS COLOR	DIMMING	FIXTURE LENGTH	BEAM ANGLE	VOLTAGE	HOUSING COLOR	CANOPY	GLOSS LEVEL	COLOR RENDERING INDEX																																																																
<table border="1"> <tr><th colspan="2">TYP - LUMINOUS COLOR</th></tr> <tr><td>PW30</td><td>pureWhite - 3000 K</td></tr> <tr><td>PW40</td><td>pureWhite - 4000 K</td></tr> </table>	TYP - LUMINOUS COLOR		PW30	pureWhite - 3000 K	PW40	pureWhite - 4000 K	<table border="1"> <tr><th colspan="2">DIMMING</th></tr> <tr><td>NDIM</td><td>Non-dimmable</td></tr> <tr><td>TRIAC</td><td>Dimmable - TRIAC</td></tr> </table>	DIMMING		NDIM	Non-dimmable	TRIAC	Dimmable - TRIAC	<table border="1"> <tr><th colspan="2">FIXTURE LENGTH</th></tr> <tr><td>1/310</td><td>310 mm / 12.2 in</td></tr> <tr><td>1/465</td><td>465 mm / 18.31 in</td></tr> </table>	FIXTURE LENGTH		1/310	310 mm / 12.2 in	1/465	465 mm / 18.31 in	<table border="1"> <tr><th colspan="2">BEAM ANGLE</th></tr> <tr><td>18X18</td><td>18° x 18°</td></tr> <tr><td>26X26</td><td>26° x 26°</td></tr> <tr><td>35X35</td><td>35° x 35°</td></tr> </table>	BEAM ANGLE		18X18	18° x 18°	26X26	26° x 26°	35X35	35° x 35°	<table border="1"> <tr><th colspan="2">VOLTAGE</th></tr> <tr><td>110V</td><td>90 - 135 VAC 50/60 Hz</td></tr> <tr><td>230V</td><td>180 - 264 VAC 50/60 Hz</td></tr> <tr><td>277V</td><td>277 VAC 50/60 Hz</td></tr> </table>	VOLTAGE		110V	90 - 135 VAC 50/60 Hz	230V	180 - 264 VAC 50/60 Hz	277V	277 VAC 50/60 Hz	<table border="1"> <tr><th colspan="2">HOUSING COLOR</th></tr> <tr><td>WH</td><td>Signal white RAL 9003</td></tr> <tr><td>JB</td><td>Jet black RAL 9005</td></tr> <tr><td>PG</td><td>Dark grey RAL 9023</td></tr> <tr><td>GB</td><td>Grey brown RAL 8019</td></tr> <tr><td>GO</td><td>Gold RAL 1036</td></tr> </table>	HOUSING COLOR		WH	Signal white RAL 9003	JB	Jet black RAL 9005	PG	Dark grey RAL 9023	GB	Grey brown RAL 8019	GO	Gold RAL 1036	<table border="1"> <tr><th colspan="2">CANOPY</th></tr> <tr><td>MP</td><td>Monopoint</td></tr> <tr><td>TR</td><td>Trackmount</td></tr> </table>	CANOPY		MP	Monopoint	TR	Trackmount	<table border="1"> <tr><th colspan="2">GLOSS LEVEL</th></tr> <tr><td>MA</td><td>Matt</td></tr> <tr><td>HG</td><td>High Gloss Finished</td></tr> </table>	GLOSS LEVEL		MA	Matt	HG	High Gloss Finished	<table border="1"> <tr><th colspan="2">COLOR RENDERING INDEX</th></tr> <tr><td>RA80</td><td>CRI 80</td></tr> <tr><td>RA97</td><td>CRI 97</td></tr> </table>	COLOR RENDERING INDEX		RA80	CRI 80	RA97	CRI 97
TYP - LUMINOUS COLOR																																																																								
PW30	pureWhite - 3000 K																																																																							
PW40	pureWhite - 4000 K																																																																							
DIMMING																																																																								
NDIM	Non-dimmable																																																																							
TRIAC	Dimmable - TRIAC																																																																							
FIXTURE LENGTH																																																																								
1/310	310 mm / 12.2 in																																																																							
1/465	465 mm / 18.31 in																																																																							
BEAM ANGLE																																																																								
18X18	18° x 18°																																																																							
26X26	26° x 26°																																																																							
35X35	35° x 35°																																																																							
VOLTAGE																																																																								
110V	90 - 135 VAC 50/60 Hz																																																																							
230V	180 - 264 VAC 50/60 Hz																																																																							
277V	277 VAC 50/60 Hz																																																																							
HOUSING COLOR																																																																								
WH	Signal white RAL 9003																																																																							
JB	Jet black RAL 9005																																																																							
PG	Dark grey RAL 9023																																																																							
GB	Grey brown RAL 8019																																																																							
GO	Gold RAL 1036																																																																							
CANOPY																																																																								
MP	Monopoint																																																																							
TR	Trackmount																																																																							
GLOSS LEVEL																																																																								
MA	Matt																																																																							
HG	High Gloss Finished																																																																							
COLOR RENDERING INDEX																																																																								
RA80	CRI 80																																																																							
RA97	CRI 97																																																																							

Sample Order Code: FUN-M-R-20-PW30-NDIM-1/310-35X35-110V-JB-MP-MA-RA80-Y01

\* Project-specific options are available - Please contact our Sales Representative for further information.