



funis m surface round

pureWhite

SPECIFICATION SHEET

BION TECHNOLOGIES a brand of ONELED.DE GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2013, BION TECHNOLOGIS is a brand of ONELED.DE GMBH
All rights reserved / Subject to change / Specifications may change without notice.

www.biontechnologies.com

Project	Fixture#	Date
		Firm



Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

funis-m-sf-round- _____ - _____ - _____ - _____ - _____ - _____ - _____ - Y01

TYP - LUMINOUS COLOR		DIMMING		FIXTURE LENGTH		BEAM ANGLE		VOLTAGE		HOUSING COLOR		GLOSS LEVEL		COLOR RENDERING INDEX	
TYP - LUMINOUS COLOR		DIMMING		FIXTURE LENGTH		BEAM ANGLE		VOLTAGE		HOUSING COLOR		GLOSS LEVEL		COLOR RENDERING INDEX	
pW30	pureWhite - 3000 K	ndim	Non-dimmable	1/155	155 mm / 6.1 in	18x18	18° x 18°	110V	90 - 135 VAC 50/60 Hz	WH	Signal white RAL 9003	MA	Matt	RA80	CRI 80
pW40	pureWhite - 4000 K	dim-TRIAC	Dimmable - TRIAC	1/310	310 mm / 12.2 in	26x26	26° x 26°	230V	180 - 264VAC 50/60 Hz	JB	Jet black RAL 9005	HG	High Gloss Finished	RA97	CRI 97
				1/465	465 mm / 18.31 in	35x35	35° x 35°	277V	277 VAC 50/60 Hz	PG	Dark grey RAL 9023				
										GB	Grey brown RAL 8019				
										GO	Gold RAL 1036				

Sample Order Code: funis-m-sf-round-pW30-ndim-44x44-230V-WH-MA-RA80-Y01

* Project-specific options are available - Please contact our Sales Representative for further information.