



linea m hp indoor

tunableWhite

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm

Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

LIN-M-HP-IN- _____ - _____ - _____ - _____ - _____ - _____ - Y03

TYP - LUMINOUS
COLOR

DIMMING

BEAM ANGLE

HOUSING COLOR

LEADERCABLE
LENGTH

GLARE
PROTECTION

MOUNTING
OPTION

TYP - LUMINOUS COLOR

HOUSING COLOR

AA Aluminium anodized (Standard)

BA Black anodized

DIMMING

BEAM ANGLE

8X8 8° x 8°

10X10 10° x 10°

23X23 23° x 23°

43X43 43° x 43°

52X52 52° x 52°

8X31 8° x 31°

10X42 10° x 42°

12X60 12° x 60°

14X100 14° x 100°

30X60 30° x 60°

20X60Y10R 20° x 60° (Tilt in C0-plane: 10°)

20X60Y10L 20° x 60° (Tilt in C0-plane: -10°)

LEADERCABLE LENGTH

ETE End to end - wiring

003 + 30 cm (ca. 1 ft)

006 + 60 cm (ca. 2 ft)

009 + 90 cm (ca. 3 ft)

012 + 1,2 m (ca. 4 ft)

GLARE PROTECTION

OP No glare protection

HL Hex louver (internal)

LL0 Linear louver (internal)

MOUNTING OPTION

MPA Mounting Plate Basic

MSH Mounting Set Hinge

Sample Order Code: linea-m-hp-in-tw3060-dim-DMX-4/1228-8x8-AA-Y01

* Project-specific options are available - Please contact our Sales Representative for further information.