



tantulus 24V hp100

pureWhite

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

| | | |
|----------------|-----------------|-------------|
| Project | Fixture# | Date |
| | | Firm |



Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

TAN-24V-HP100- _____ - _____ - _____ - Y31

TYP - LUMINOUS
COLOR

FIXTURE LENGTH

BEAM ANGLE

MOUNTING
OPTION

| TYP - LUMINOUS COLOR | |
|----------------------|--------------------|
| PW20 | pureWhite - 2000 K |
| PW22 | pureWhite - 2200 K |
| PW25 | pureWhite - 2500 K |
| PW27 | pureWhite - 2700 K |
| PW30 | pureWhite - 3000 K |
| PW35 | pureWhite - 3500 K |
| PW40 | pureWhite - 4000 K |
| PW45 | pureWhite - 4500 K |
| PW50 | pureWhite - 5000 K |
| PW57 | pureWhite - 5700 K |
| PW65 | pureWhite - 6500 K |

| FIXTURE LENGTH | |
|----------------|--------------------|
| 310 | 310 mm / 12.2 in |
| 415 | 415 mm / 16.34 in |
| 515 | 515 mm / 20.28 in |
| 615 | 615 mm / 24.21 in |
| 720 | 720 mm / 28.35 in |
| 820 | 820 mm / 32.28 in |
| 920 | 920 mm / 36.22 in |
| 1025 | 1025 mm / 40.35 in |
| 1125 | 1125 mm / 44.29 in |
| 1225 | 1225 mm / 48.23 in |
| 1330 | 1330 mm / 52.36 in |
| 1430 | 1430 mm / 56.3 in |
| 1530 | 1530 mm / 60.24 in |
| 1635 | 1635 mm / 64.37 in |
| 1735 | 1735 mm / 68.31 in |
| 1835 | 1835 mm / 72.24 in |

| BEAM ANGLE | |
|------------|-------------------|
| 30X120(F) | 30° x 120° frost |
| 60X120(F) | 60° x 120° frost |
| 90X120(F) | 90° x 120° frost |
| 120X120(C) | 120° x 120° clear |
| 120X120(F) | 120° x 120° frost |
| 120X120(W) | 120° x 120° white |
| SQR(W) | 186° x 110° white |

| MOUNTING OPTION | |
|---|-------------------|
| K0 | Bracket Set 0° |
| K15 | Bracket Set 15° |
| K30 | Bracket Set 30° |
| K45 | Bracket Set 45° |
| K60 | Bracket Set 60° |
| KADJ | Positioning Hinge |
| Fixed Angle: Bracket count: 2 <= 1225 mm (48.23 in) > 3 HKadj: Bracket count: 2 for all lengths | |

Sample Order Code: TAN-24V-HP100-PW20-820-120X120(C)-K45-Y31

* Project-specific options are available - Please contact our Sales Representative for further information.