



# tantulus eco outdoor

pureWhite

SPECIFICATION SHEET

## BION TECHNOLOGIES GMBH

Lindberghstrasse 15  
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0  
Fax: +49 (0)8231/95787-29

[www.biontechnologies.com](http://www.biontechnologies.com)  
[info@biontechnologies.com](mailto:info@biontechnologies.com)

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH  
All rights reserved / Subject to change / Specifications may change without notice.

|         |          |      |
|---------|----------|------|
| Project | Fixture# | Date |
|         |          | Firm |

## Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

TAN-OUT-ECO- \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - Y31

TYP - LUMINOUS  
COLOR

FIXTURE LENGTH

BEAM ANGLE

MOUNTING  
OPTION

| TYP - LUMINOUS COLOR |                    |
|----------------------|--------------------|
| PW26                 | pureWhite - 2600 K |
| PW33                 | pureWhite - 3300 K |
| PW40                 | pureWhite - 4000 K |
| PW44                 | pureWhite - 4400 K |
| PW54                 | pureWhite - 5400 K |

| MOUNTING OPTION   |                   |
|---|-------------------|
| K0  | Bracket Set 0°    |
| K15   | Bracket Set 15°   |
| K30   | Bracket Set 30°   |
| K45   | Bracket Set 45°   |
| K60   | Bracket Set 60°   |
| KADJ  | Positioning Hinge |
| Fixed Angle:<br>Bracket count: 2 <= 1225 mm (48.23 in) > 3<br>HKadj: Bracket count: 2 for all lengths |                   |

| FIXTURE LENGTH |                    |
|----------------|--------------------|
| 310            | 310 mm / 12.2 in   |
| 615            | 615 mm / 24.21 in  |
| 920            | 920 mm / 36.22 in  |
| 1225           | 1225 mm / 48.23 in |
| 1530           | 1530 mm / 60.24 in |
| 1835           | 1835 mm / 72.24 in |

| BEAM ANGLE |                   |
|------------|-------------------|
| 30X120F    | 30° x 120° frost  |
| 120X120W   | 120° x 120° white |
| 120X120F   | 120° x 120° frost |

\* Project-specific options are available - Please contact our Sales Representative for further information.