



tellus m eco

tunableWhite

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm

Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

TEL-M-ECO- TW3060 - - - - - - Y03

TYP - LUMINOUS
COLOR

DIMMING

FIXTURE LENGTH

BEAM ANGLE

WIRING

GLARE
PROTECTION

TYP - LUMINOUS COLOR	
TW3060	tunableWhite - 3000 K - 6000 K

BEAM ANGLE	
8X8	8° x 8°
10X10	10° x 10°
23X23	23° x 23°
43X43	43° x 43°
52X52	52° x 52°
8X31	8° x 31°
10X42	10° x 42°
12X60	12° x 60°
14X100	14° x 100°
WWW	30° x 58° (Tilt in C0-plane: -14°)
WWN	30° x 11° (Tilt in C0-plane: -14°)
MARKER	110° x 110° Marker

GLARE PROTECTION	
OP	No glare protection
HL	Honeycomb louver
LL17	Linear louver 17°
LL00	Linear louver 0°
CGC	customized glare control
Use LL17 only with beam angle www or wwn	

DIMMING	
DMX	Dimmable - DMX
IOT	Dimmable - IOT

FIXTURE LENGTH	
345	345 mm / 13.58 in
650	650 mm / 25.59 in
955	955 mm / 37.6 in
1260	1260 mm / 49.61 in

WIRING	
CE	Europe
ETL	North America

Sample Order Code: [tellus-m-eco-tw3065-dim-DMX-4/1260-10x10-cETLus-Y01](#)

* Project-specific options are available - Please contact our Sales Representative for further information.